

**HMRZ.EX16373**
Gate Valves[Page Bottom](#)**Gate Valves**[See General Information for Gate Valves](#)**GALA RS INC**

EX16373

Suite 201

11200 Westheimer Rd

Houston, TX 77042 USA

Resilient Seated Gate Valves.

Pattern	Model	Size, in.	End Configuration	Rated Pressure, psig
*NRS	388FF-300	2.5, 3, 4, 5, 6, 8, 10, 12	F by F	300
	388GG-300		G by G	
	388FG-300		F by G	
O,S&Y	399FF-300	2, 2.5, 3, 4, 5, 6, 8, 10, 12	F by F	300
	399GG-300		G by G	
	399FG-300		F by G	
*NRS	388FF-250	2.5, 3, 4, 5, 6, 8, 10, 12	F by F	250
	388GG-250		G by G	
	388FG-250		F by G	
O,S&Y	399FF-250	2, 2.5, 3, 4, 5, 6, 8, 10, 12	F by F	250
	399GG-250		G by G	
	399FG-250		F by G	
*NRS	388FF-200	2.5, 3, 4, 5, 6, 8, 10, 12	F by F	200
	388GG-200		G by G	
	388FG-200		F by G	
O,S&Y	399FF-200	2, 2.5, 3, 4, 5, 6, 8, 10, 12	F by F	200
	399GG-200		G by G	
	399FG-200		F by G	

*NRS valve provided with a Post Indicator Flange.

[Last Updated](#) on 2013-07-01[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".