

USQT.S309 - Extinguishing System Attachments

Extinguishing System Attachments

POTTER ELECTRIC SIGNAL CO L L C

S309

1609 PARK 370 PL

HAZELWOOD, MO 63042-4417 United States

SPRINKLER SYSTEM ALARM INITIATING DEVICES

WET PIPE, PADDLE TYPE

Model	Size In.	Pipe Schedule	Max System Pressure psig
VSG	2, 2-1/2, 3, 4	Water Mist	450
		Systems Only	
VSR-F, VSR-FE,	2, 2-1/2, 3,	10-40	450
VSR-FE-2, VS-F	3-1/2, 4, 5,	Steel	
	6, 8, 10		
VSR, VSR-CR	2, 2-1/2, 3, 3-1/2,	10-40 Steel	450
	4, 5, 6, 8, 10		
VSR-AT	2, 2-1/2, 3, 3-1/2,	10-40 Steel	450
	4, 5, 6, 8		
VSR-EU	2, 2-1/2, 3, 4, 5, 6, 8	10-40 Steel	450
VSR-S, VSR-S (EU)	1, 1-1/4, 1-1/2, 2	10-40 Steel	300
		Listed Plastic	
		K, L, M Copper	
VSR-SF, VS-SP, VS-SPB	1, 1-1/4, 1-1/2, 2	10-40 Steel	250
		Listed Plastic	
		K, L, M Copper	

VSR-CF, VSR-C	2, 2-1/2, 3,	Listed Plastic	175
	2, 2-1/2, 3, 4	K,L,M Copper	
VSR-SFG, VSR-SG, VSR-SFT, VSR-ST	1, 1-1/4, 1-1/2, 2	Listed Plastic	250
WFD20EXP	2	10-40 Steel	450
WFD25EXP	2.5	10-40 Steel	450
WFD30-2EXP	3	10-40 Steel	450
WFD35EXP	3.5	10-40 Steel	450
WFD40EXP	4	10-40 Steel	450
WFD50EXP	5	10-40 Steel	450
WFD60EXP	6	10-40 Steel	450
WFD80EXP	8	10-40 Steel	450

Wet-pipe sprinkler system attachments: Water-flow indicators (paddle type), suitable for indoor and outdoor installation shipped without "U" bolts and nuts to Victaulic customer. Models may be single or bulk-packaged. The packing cartons will also include the assigned Victaulic Part Code on the exterior.

Model WFD20VN with Victaulic Part Code CXS020747020.

Model WFD25VN with Victaulic Part Code CXS024747022.

Model WFD30VN with Victaulic Part Code CSX030747N23.

Model WFD40VN with Victaulic Part Code CXS040747025.

Model WFD60VN with Victaulic Part Code CXS060747027.

Wet-pipe sprinkler system attachments: Water-flow indicators (paddle type):

Model	Size In.	Pipe Schedule	Max Working Pressure psig
WFD20VN	2	Victaulic Risers	450
WFD25VN	2-1/2	Victaulic Risers	450
WFD30VN	3	Victaulic Risers	450
WFD40VN	4	Victaulic Risers	450
WFD60VN	6	Victaulic Risers	450

WFD20N, WFD20NA	2	7, 10, 40	450
WFD25N, WFD25NA	2-1/2	7, 10, 40	450
WFD30N, WFD30NA	3	7, 10, 40	450
WFD40N, WFD40NA	4	7, 10, 40	450
WFD50N, WFD50NA	5	10, 40	450
WFD60N, WFD60NA	6	10, 40	450
WFD80N, WFD80NA	8	10, 40	450
WFDTN, WFDTNA, WFDTVN, WFDTNRN, RFDTHN	Threaded Brass or steel: 1, 1-1/4, 1-1/2, 2 Copper Sweat Tees: 1, 1-1/4, 1-1/2, 2 Tyco, Spears, Victaulic and NIBCO brand Chlorinated Polyvinyl Chloride: 1		375
WFDNFS, WFDNFSA	SPEARS brand Chlorinated Polyvinyl Chloride: 1, 1-1/4, 1-1/2, 2 NIBCO brand Chlorinated Polyvinyl Chloride: 1, 1-1/4, 1-1/2, 2 TYCO brand Chlorinated Polyvinyl Chloride: 1, 1-1/4, 1-1/2, 2 IPEX brand Chlorinated Polyvinyl Chloride: 1, 1-1/4, 1-1/2, 2		175
WFDNFT, WFDNFTA	Steel/Brass Threaded: 1, 1-1/4, 1-1/2, 2 Copper Sweat Tees: 1, 1-1/4, 1-1/2, 2 NIBCO brand Chlorinated Polyvinyl Chloride: 1 "CPVC SPEARS w/Metal Band": 1, 1-1/2 "CPVC SPEARS w/Brass Insert": 1 TYCO brand Chlorinated Polyvinyl Chloride: 1		175

The WFD Series waterflow indicators employ an enclosure that was evaluated for Type NEMA 4/IP 54 rating.

Model VS-SP, VS-SPB for outdoor use with Kit No. 1940037. Models VS-F, VSR-F, VSR-CF, VSR-C, VSR-FE, VSR-FE-2 for outdoor use with Kit No. 1940036.

DRY-PIPE & WET-PIPE, PRESSURE TYPE

Model	Oper Pressure psig	Max System Pressure psig
*PS-10	0-20	300
*PS-10A	4-8	300
*PS-100	20-225	300
*PS10-1	4-15	300
*PS10-1A	4-20	250
*PS10-2	4-15	300
*PS10-2A	4-20	250

*PS10-1 w/Brass Bushing	4-15	300
*PS10-2 w/Brass Bushing	4-15	300
*PS-100A	20-175	300
*PS100-2	25-175	300
*PS100-2A	20-225	300
WFS-B	10	250
WFSPDB	100	250
*WFSR-C	10	250
*WFSR-F	4-8	175
QRS	10-65	175

SUPERVISORY SIGNAL INITIATING DEVICES

PRESSURE DEVICES

Model	Oper Pressure psig	Max System Pressure psig
*PS-40	20-225	300
PS15-2	5-30	300
*PS-40A	20-175	300
*PS40-1	10-60	300
*PS40-1A	20-175	300
*PS40-2A	20-175	300
*PS25-2	10-60	300
*PS40-2	10-60	300
*PS40-1 w/Brass Bushing	10-60	300
*PS40-2 w/Brass Bushing	10-60	300
HLS-B	40	250
*PS-120	20-225	300
*PS-120A	20-175	300
*PS120-1	25-175	300

*PS120-1A	20-175	300
*PS120-2	25-175	250
*PS120-2A	20-175	300
*PS120-1 w/Brass Bushing	35-225	300
*PS120-2 w/Brass Bushing	35-225	300
EPS10EXP	4-20	250
EPS40EXP	10-100	250
EPS120EXP	10-200	250
EPS10-1	4-20	300
EPS10-2	4-20	300
EPS40-1	10-100	300
EPS40-2	10-100	300
EPS120-1	10-200	300
EPS120-2	10-200	300

CONTROL VALVE DEVICES

Gate Valve	Post Indicator Valve
GVS	PIVS-B
OSYS-B	PIBV2
*OSYSU-1, -2	*PCVS-1, -2
OSY2	

Accessory, Cover Tamper Switch Kit, Model PSCTSK for use with the PS Series Pressure Switches.

PTS-B Plug Type Switch — Special Application

*PMS Plug Type Switch — Special Application

*PTS-C Plug Type Switch — Special Application.

BVS-1", -3/4", -1/2" Supervised Trim Valves.

RBVS — Retro-fit Ball Valve Supervisory Switch.

SUPERVISORY WATER TEMPERATURE DEVICES Steel or Wood Tank

*TTS-S, TTS-W

SUPERVISORY AIR TEMPERATURE DEVICES

RTS-C, RTS-O, for indoor use.

WATERLEVEL DEVICES

*WLS-S (Steel Tank), WLS-W (Wood Tank), WCS

*For indoor or outdoor use.

VALVE SUPERVISORY SWITCH

*PSP1

Trademark and/or Tradename:  **Safe Signal™**

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."